

The new Demag DC^{COM} chain hoist
2 speeds for the price of 1



Two Speeds Standard For The Price Of One

2 for 1



The DC^{COM} is the perfect choice to meet your material handling requirements!!

The DC^{COM} is equipped with standard two speed motors, economically priced to meet your material handling requirements.



Connections for the pendant and supply power simplifies installation and provides versatility to relocate the hoist for other applications.

The field adjustable push button provides 10 ft of adjustment to easily adapt to your operators ergonomic requirements.

The push button pendant is compact and lightweight with buttons that are easy to depress. The cable also flexes easily so that the pendant can always be held in a comfortable position. This ergonomic design significantly reduces the risk of repetitive motion injuries.

Installation is quick with the easy access maintenance panel. Behind which you will find access to the chain lubrication point, the power quick disconnect and the 10 ft of push button cable storage.



The control pendant features a plug-in design and can be easily replaced, if needed.

The unique chain guide, with five or six pocket sprocket, provides smooth hoist operation.

Standard Upper and Lower limit switches protect the hoist from unexpected over travels.

The die cast aluminum gearbox and motor, along with the electrical and fan impact resistant covers, protect the hoist's critical components.



The hoist comes complete with the following:

- Control Cable and DSC control pendant
- Chain collector container
- Chain Lubrication (Shipped Loose)
- Quick Disconnect for supply power (Shipped Loose)
- Operating Instructions
- Suspension Lug
- Upper & Lower Limit Switches
- 24V Control Voltage
- Rated For Outdoor Use (IP 55)
- 2 Year Warranty

Adjust Up To 10 ft

The length of the control cable can be adjusted without the need for any wiring.

SWL Lb (kg)	Chain Hoist Type	Hoist Speed at 60 Hz ft/min (m/min)	Hook Path ft (m)	FEM Group of Mechanisms	Reeving
275 (125)	DC ^{COM} 1	32/8 (9.6/2.4)	16 (5)	2m	1/1
550 (250)	DC ^{COM} 2	16/8 (4.8/2.4)		1Am	
1100 (500)	DC ^{COM} 5				
2200 (1000)	DC ^{COM} 10	16/4 (4.8/1.2)			
4400 (2000)	DC ^{COM} 20			2/1	

IP 55 enclosure, 40% and 60% duty factors

Demag Cranes and Components

29201 Aurora Road
Cleveland, Ohio 44139
Telephone: (440) 248-2400
Telefax: (440) 248-3086
Internet: <http://www.demag-us.com>